

UCOTILE-MA ST-174

Polymer Modified Marble Adhesive

Product

UCOTILE-MA is a single pack ready to use waterproof marble adhesive.

Composition

UCOTILE-MA is a blend of specially selected polymers cement and fillers.

Description

UCOTILE-MA is ready to use excellent water proof marble adhesive used for permanent fixing of marbles requires only addition of water.

Benefits

1. Excellent Bond

UCOTILE-MA ensure excellent bond on concrete plastered and even on smooth surfaces.

2. Economy

UCOTILE-MA is ready to use with conventional masonry tools. It require only addition of water eliminate site mixing of cement and aggregates.

UCOTILE - MA is to be applied at the thickness of 3 mm to 4 mm that reduce in time and labour.

Technical Data

Form	Powder
Colour	White
W/P Ratio	0.3

Advantages

- Excellent adhesion to smooth surface
- Good waterproofing characteristics
- Ready to use
- Easy to apply with conventional tools
- No curing required
- Cost effective

Purpose

For permanent fixing of Marble

Where to Use

For fixing of Marbles

Method of Use

The substrate should be sound clean and free from contamination. UCOTILE-MA should be mixed with water in the ratio of 3:1 by volume. Mix thoroughly to form a creamy mortar applies this mortar at 3 mm to 4 mm uniform thickness.

Remove excessive material with a clean cloth before material has set.

Coverage

One 25 gm pack will cover 6m² - 7.5 m² with 3 mm to 4 mm thickness.

Packing

UCOTILE-MA is supplied in 25 KG bags and 50 KG paper laminated / woven sacks.

Storage

- UCOTILE-MA has a shelf life of 12 months from the date of manufacturing, if stored as per manufacturer's instructions &in manufacturer's original unopened packing.
- Keep away from direct sunlight and store in dry & shade.
- Protect from freezing and moisture.

Handling Precaution

- UCOTILE-MA is an industrial chemical; required handling precautions should be followed.
- UCOTILE-MA is non-flammable and doesn't contain any flammable ingredient.
- UCOTILE-MA is non-hazardous, however inhalation of its dust particles should be avoided. Use of facemask is recommended.
- Prolonged contact with skin should be avoided. Use rubber gloves and boots, when working overhead, goggles should be worn.
- Contact with eye should be avoided. If in contact with eye, wash with water and take medical advice immediately.

Important Note:

All products should be used in accordance with manufacturer's instructions. Every effort is made to ensure that the information is reliable, however we do not accept any responsibility for any work carried out with our material(s) as we have no control over the method(s) used for application, site conditions, weather conditions, etc.



Works:

Plot No. 16, GIDC Industrial Estate, Pardi – 396125, Dist. Valsad, GJ, IND +91 99250 35219 | info@innovativemarketing.in | www.innovativemarketing.in

Marketed by:

